

Premium Resin Ribbon


TDR345

Excellent printing quality
Superior media adaptability
Superior corrosion resistance


TDR345, as a high-performance, cost-effective resin ribbon. With high printing blackness, excellent media adaptability and alcohol resistance. It is widely used in electrical appliances, equipment, electronics and other industries and received wide acclaim.

Printing Quality


Darkness




0° barcode



90° barcode




Sharpness



Min. printable character




Graphics




Substrate Compatibility

Recommended substrate grades




Sensitivity

Printing speed



Printing temperature



Resistance Test

Resistance test

Slight exposure begins after approx. X cycles with a 680G weight load

Smudge resistance



Scratch resistance



Alcohol



95% Industrial alcohol

Gasoline



92 # Gasoline

Braking fluid



Bosch dot4 plus

Water resistance test

With a printed label, soaked in 100°C water for 2 hours, observe its color fading




Low-temperature test

With a printed label in a closed chest at -17°C for 20 hours, observe its stripping























Premium Resin Ribbon

TDR345



Recommended Applications

 Receipt and delivery labels for warehouses	 Logistics	 Pharmaceuticals	 Daily chemicals
 Pre-packaging	 Refrigeration Industry	 Hot working	 Retail labels
 Digital & electronics labels	 Clothing tags	 Labels for automobile industry	 Chemical industry
 Nursery gardens and flowers	 Production lines	 Wooden products	 Steel & iron manufacturing
 Fixed assets	 Electrical equipment	 Mechanical equipment	 Luggage

Certifications And Permits

 ROHS2.0	 REACH	 ISO9001/14001	 MSDS
--	--	--	---

HALOGEN

HALOGEN

Properties

PET film

Thickness: 4.5µm

Ribbon

Thickness: 8.0±0.3µm


Ink

Color: Black Melting point: 100±3°C

Storage condition

Temperature: 5-35°C Humidity: 20-80%
Validity period: 12 months

Product Comparison



Todaytec

All product specifications are accessible at our website www.todaytec.com.cn.

Hangzhou Todaytec Digital Co.,Ltd
Add:600 KangXin Rd HangZhou Qianjiang Economy Development Zone LinPing
Hangzhou 311106 China
Tel:+86 571 86358910